

Certificate of Mailing by "Express Mail"	
Express Mailing No.:	EM794167624 43
Date of Deposit:	12/21/01
I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office Box Addressee" Under 37 C.F.R. \$1.10 on the date indicated above addressed to The Assistant Commissioner for Patents, Washington, D.C. 20231.	
<i>Sydney E. Sexton</i>	

IMPROVED INTERFACE FOR A TELECOMMUNICATION SYSTEM

Background of the Invention

5 This invention is generally directed to an improved interface for use in connection with a telecommunication system. A telecommunication system often includes a telephone switching system and an adjunct processor such as a voice messaging system (VMS).

10 The telephone switching system processes messages from multiple telephones and their users. These messages are often further processed and stored in the VMS.

15 Messages in the telecommunication system are comprised of a voice component and a data message component. The voice component relates to the voice message which has been recorded and the data component identifies information, such as, where the call originated, the destination of the call, and the time of the call. The present invention relates only to the processing of the data component of the messages.

A problem which is often encountered in a telecommunication system is that the telephone switching system utilizes a different protocol than the adjunct processor. A protocol is a set of rules governing the format of data which is exchanged between microprocessors. Two types of protocols, for example, are Application Processor Interface (API) and Simplified Message Service Interface (SMSI). In order for data messages to be forwarded from the telephone switch to the adjunct processor, the microprocessor within the adjunct processor must recognize the protocol of the data messages from the telephone switch. Likewise, in order for data messages to be forwarded from the adjunct processor to the telephone switch, the microprocessor within the telephone switch must recognize the protocol of the data messages from the adjunct processor. Often however, telecommunication switches and adjunct processors do not utilize the same protocol. For example, many switches operate using API protocol and many VMS operate using SMSI protocol. In order for the VMS and the telecommunication switch to operate together an interface (or protocol converter) is needed to convert the API protocol messages delivered from the switch to SMSI protocol. Once the data is formatted in SMSI protocol, the data can be utilized by the VMS. Similarly, the data delivered from the VMS is converted from SMSI protocol to API protocol so that it may be utilized by the switch.

In the past, interfaces have been used to accomplish the translation of data messages between telephone switches and VMS. A number of problems, however, have been encountered when these interfaces are implemented. First, the number of messages which can be transmitted between the switch and the VMS is limited by the capacity

of the interface. Another problem is the failure of the transmission link provided by the interface. Because all messages to be processed by the VMS must be transmitted through the interface's single link, if the link fails, no messages can be delivered to the VMS. Moreover, when links fail it is often difficult to determine the cause of the failure.

Previously the problems of link failure have been solved by connecting an additional interface between the telephone switch and the VMS. The use of a second interface, however, doubles the cost of the system and the space required for housing the system. Additionally, although additional capacity is provided by the second interface, this additional capacity is often unnecessary. In many situations, the capacity provided by a single interface is sufficient to meet the demands of the system. The problem rather lies in failure of the link provided by the interface and the inability of the interface to process and translate data messages upon failure of the link.

The present invention provides an improved interface which overcomes the problems presented in the prior art and which provides additional advantages over the prior art, such advantages will become clear upon a reading of the attached specification in combination with a study of the drawings.

Objects and Summary of the Invention

An object of the present invention is to provide an interface with improved performance;

5 Another object of the present invention is to provide an interface with improved reliability;

10 A further object of the present invention is to provide an interface which improves the performance and reliability of the system while minimizing the number of electrical connections between the interface and the adjunct processor; and

A further object of the present invention is to provide a cost efficient interface.

15 Briefly, and in accordance with the foregoing, the present invention discloses an improved interface between a telephone switching system and an adjunct processor. The interface provided by the present invention allows for improved performance and reliability. The improved performance and reliability are achieved by utilizing multiple transmission links for processing data messages
20 between the telephone switching system and the adjunct processor and by implementing unique operating software to selectively and automatically control the data transmission and retransmission of the data along the links. If one transmission link fails, all messages are
25 processed by the remaining link or links.

Brief Description of the Drawings

The organization and manner of the structure and operation of the invention, together with further objects and advantages thereof, may best be understood by reference to the following description, taken in connection with the accompanying drawings, wherein like reference numerals identify like elements in which:

FIGURE 1 is a block diagram representing a portion of a telecommunications system in which the interface of the present invention is used;

FIGURE 2a is a front perspective view of an embodiment of the interface of the present invention;

FIGURE 2b is a rear perspective view of the interface of the present invention;

FIGURE 3 is a block diagram representing the processing of messages by the interface between a telephone switch and a VMS;

FIGURE 4a is an outline of the steps performed by the device driver algorithm of the interface of the present invention when processing messages in the forward direction;

FIGURE 4b is an outline of the steps performed by the protocol stack algorithm of the interface of the present invention when processing messages in the forward direction;

FIGURE 4c is an outline of the steps performed by the splitting task algorithm of the interface of the present invention;

5 FIGURE 4d is an outline of the steps performed by the application task algorithm of the interface of the present invention when processing messages in the forward direction;

10 FIGURE 4e is an outline of the steps performed by the application task algorithm of the interface of the present invention when processing messages in the reverse direction;

15 FIGURE 4f is an outline of the steps performed by the combining task algorithm of the interface of the present invention;

20 FIGURE 4g is an outline of the steps performed by the protocol stack algorithm of the interface of the present invention when processing data messages in the reverse direction; and

FIGURE 4h is an outline of the steps performed by the device driver algorithm of the interface of the present invention when processing data messages in the reverse direction.

Detailed Description of the Preferred Embodiment

While the invention may be susceptible to embodiment in different forms, there is shown in the drawings, and herein will be described in detail, a specific embodiment
5 with the understanding that the present disclosure is to be considered an exemplification of the principles of the invention, and is not intended to limit the invention to that as illustrated and described herein.

As shown in FIGURE 1, the interface 10 of the present
10 invention is to be used in a telecommunication system. The telephone switching system 14 provides communication services for a number of telephones 12 and their users. One type of switch 14 typically used in a telecommunication system is the 5ESS switch made by
15 Lucent Technologies, for example. The interface 10 provides a connection for the transmission of data messages from the telephone switching system 14 to the adjunct processor 18 and from the adjunct processor 18 to the telephone switching system 14. The adjunct processor
20 18 shown in FIGURE 1 is a Voice Messaging System (VMS). Although the interface 10 of the present invention could be adapted for use with other types of adjunct processors, the interface 10 of the present invention will be shown and described in connection with a VMS.

25 The present invention will be described in the context of a VMS which utilizes SMSI protocol and a telephone switch which utilizes API protocol, although it is to be understood that the present invention can be used with a telephone switch and adjunct processor which utilize any
30 protocol. Because the telephone switch 14 the VMS 18 do not utilize the same protocol, the interface 10 of the present invention provides the necessary translation.

Within the context of this description of the invention, when the interface 10 receives messages from the switch 14 and delivers the messages to the VMS 18 it is said to be operating in the forward direction. When the
5 interface 10 receives messages from the VMS 18 and delivers the messages to the switch 14 it is said to be operating in the reverse direction. When operating in the forward direction, the interface 10 receives API protocol messages from the switch 14 and delivers the
10 messages to the VMS 18 in SMSI protocol. When operating in the reverse direction, the interface 10 receives SMSI protocol messages from the VMS 18 and delivers the messages to the switch 14 in API protocol.

As shown in FIGURES 2a and 2b, the interface 10 has a
15 generally rectangularly shaped housing 20 which houses the hardware and software components of the interface 10. Electrical connection of the interface 10 is provided through the rear panel 22 of the housing 20. Connectors 24a, 24b provide electrical connection between the
20 interface 10 and the switch 14. Connector 26 provides electrical connection between the interface 10 and the VMS 18. Power is supplied to the interface 10 through a power cord 28. In the preferred embodiment, an additional connector 30 is provided for allowing
25 electrical connection of a diagnostic device.

The front panel 32 of the interface housing 20 includes several light emitting diodes (LEDs). A power LED 34 indicates whether power has been provided to the interface 10. Port status LEDs 36 provide indication of
30 which connectors 24a, 24b 30 are in use. Link status LEDs 38 provide indication that data is being transmitted over the particular link indicated.

FIGURE 3 is a diagram which represents the hardware connections between the switch 14, the interface 10 and the VMS 18. Unlike prior art interfaces, multiple electrical connections between the interface 10 and the switch 14 are provided by, for example, the connectors 24a, 24b which allow for the processing of data messages over multiple links. The connector 26 provides connection between the interface 10 and the VMS 18.

Although it is fully contemplated that the interface can provide more than two transmission links, for purposes of clarity in explanation, the invention will be described below as including only two transmission links. The processing of the data messages by the software component of the interface 10 is also shown in FIGURE 3. The diagram shows the forward flow of data messages from the switch 14 to the VMS 18 and the reverse flow of data messages from the VMS 18 to the switch 14. The software component of the interface 10 is a series of algorithms which resides in the microprocessor of the interface 10. This microprocessor is typically mounted to a circuit board which is mounted within the housing 20 of the interface 10. The microprocessor includes flash, dynamic and RAM memory. When power is delivered to the interface 10 the algorithmic software program is copied from the flash memory, to the dynamic memory and finally to the RAM where the program is executed. The interface's program is responsible for processing and translating messages between the switch 14 and the VMS 18. The software of the interface 10 is programmed such that the interface receives and processes data through two links provided by connector 24a, 24b. The software of the interface 10 is a series of algorithms/routines which process data messages between the switch 14 and the VMS 18. Each algorithm is a series of instructions which

perform specific functions associated with processing the data messages.

5 More specifically, in the forward direction, messages packets are transmitted to the interface 10 from the switch 14 via the connectors 24a, 24b. A message packet contains data related to one or more individual messages. The message packets are processed through the two links and transmitted to the VMS 18 through the connector 26. The connectors 24a, 24b of the interface 10 are connected to the switch 14 in a customary manner, such as that provided by Lucent Technologies specification 235-900-303 which details the protocol that is being utilized, and is incorporated herein by reference.

15 Processing of the data messages includes several steps. The forward processing of messages from the switch 14 to the VMS 18 will first be described. On the first link provided by the interface, the message packets are transmitted from the switch 14 to a first device driver algorithm 42 through the connector 24a. The driver for the port is to be implemented in the form of an interrupt service routine and can process both B and D channel data. An intelligent ISDN controller chip such as the PEB 2086, manufactured by Siemens Semiconductors can be used for implementation of the ISDN port.

25 The steps performed by the device driver algorithm 42 operating in the forward direction are shown in FIGURE 4a. The device driver algorithm 42 receives the data message packets, filters erroneous frames from the message packets, and forwards the message packets to the protocol stack algorithm 44.

The protocol stack algorithm 44 validates the message packets. The steps performed by the protocol stack algorithm 44 when processing data messages in the forward direction are shown in FIGURE 4b. The protocol stack
5 algorithm 44 performs three layers of validation. The first layer of validation is comprised of basic error checking. A second layer of validation confirms that the proper protocol as directed by the connector 28a has been met. The third layer of validation confirms that the
10 proper protocol as directed by the switch 14 has been met. In the case of the 5ESS switch, the third layer of validation is to confirm that the data meets the proper API protocol. After completion of the validation by the protocol stack algorithm 44, the message packets are
15 forwarded to the splitting task algorithm 46.

The splitting task algorithm 46 splits the message packets into individual messages. The steps performed by the splitting task algorithm 46 are shown in FIGURE 4c. After splitting the message packets into individual
20 messages, the messages are forwarded to the application task algorithm 38.

The application task algorithm 48 translates the individual messages from API protocol to SMSI protocol. The steps of the application task algorithm 48 when
25 processing messages in the forward direction are shown in FIGURE 4d. After translation, the application task algorithm 48 transmits the translated messages to the VMS 18 by way of the connector 26.

On the second link provided by the interface 10, the data
30 messages are processed in the forward direction in the following manner. The message packets are transmitted from the switch 14 to a first device driver algorithm 52

through the connector 24b. The steps of the device driver algorithm 52 are shown in FIGURE 4a. The device driver algorithm 52 receives the message packets, filters erroneous frames from the message packets, and forwards
5 the message packets to the protocol stack algorithm 54. The protocol stack algorithm 54 validates the message packets. The steps performed by the protocol stack algorithm 54 is shown in FIGURE 4b. The protocol stack algorithm 54 performs three layers of validation in the
10 same manner as the protocol stack algorithm 44. After completion of the validation by the protocol stack algorithm 54, the message packets are forwarded to the splitting task algorithm 46.

The splitting task algorithm 46 splits the message
15 packets into individual messages. The steps of the splitting task algorithm are shown in FIGURE 4c. After splitting the message packets into individual messages, the messages are transmitted to the application task algorithm 48.

20 The application task algorithm 48 translates the individual messages from API protocol to SMSI protocol. The steps of the application task algorithm are shown in FIGURE 6. After translation, the application task algorithm 38 transmits the translated messages to the VMS
25 18 by way of the connector 30.

In the reverse direction the interface 10 transmits individual data messages from the VMS 18 to the interface 10. The data messages are processed in the following manner.

30 Individual messages are transmitted from the VMS 18 to the application task algorithm 38 through the connector

30. The application task algorithm translates the individual SMSI protocol messages into individual API protocol messages and forwards the messages to the combining task algorithm 56. The steps performed by the application task algorithm when processing messages in the reverse direction are shown in FIGURE 4e.

The combining task algorithm 56 combines individual API protocol messages into API protocol message packets and forwards the message packets to the protocol stack algorithms 34, 44. The combining task algorithm 46 alternates delivery of message packets between the two protocol stack algorithms 44, 54. The steps performed by the combining task algorithm 56 are shown in FIGURE 4f.

The protocol stack algorithm 44 receives the message packets from the combining task algorithm 56 and validates the message packet. The protocol stack algorithm 54 receives the message packets from the combining task algorithm 56 and validates the message packets. The steps performed by the protocol stack algorithms 44, 54 in the reverse direction is shown in FIGURE 4g.

Additional visual representations of the context and queue of each of the key tasks performed by the interface of the present invention are shown in Appendix A.

After validation, the protocol stack algorithm 44 transmits the message packets to the device driver algorithm 42 and the protocol stack algorithm 54 transmits the message packets to the device driver algorithm 52. The device driver algorithm 42 transmits the message packets to the switch 14 through the connector 24a and the device driver algorithm 52

transmits the message packets to the switch 14 through the connector 24b. The steps performed by the device driver algorithms 42, 52 when processing messages in the reverse direction are shown in FIGURE 4h.

5 Thus, in the two-link interface described a first link is formed by the connector 28a, the device driver algorithm 42, protocol stack algorithm 44, the splitting task algorithm 46, the application task algorithm 48, and the connector 26. A second link is formed by the connector
10 24b, the device driver algorithm 52, the protocol stack algorithm 54, the splitting task 46, the application task 48 and the connector 48. With the addition of the second link, the interface 10 provides improved performance in that the transmission of the data is divided between each
15 of the two links. The addition of a second link also improves the interface reliability. In the event that the first link fails, all data messages are processed by the interface through the second link. Likewise, if the second link fails, all messages are processed by the
20 interface through the first link. Unlike the prior art, the interface of the present invention can continue to operate in the event of link failure. By providing multiple links within the interface 10, for processing data between the switch 14 and the VMS 18, the
25 reliability of the interface is improved without unnecessarily increasing the cost and capacity of the interface.

The improved performance of the interface of the present invention is achieved without increasing the rack space
30 occupied by the interface. The additional connector needed to provide a two link interface can be added to rear panel 22 of the panel housing 20 without increasing the size of the panel. The additional software needed to

provide a two link interface can be accommodated on the existing circuit board within the housing 20.

If two prior art interfaces were used in an attempt to improve reliability and performance, three additional electrical connections would be needed. An additional connection would be needed between the switch 14 and the second interface, between the second interface and the VMS, and to power the second interface. The use of a two link interface however, requires only one additional electrical connection between the switch 14 and the interface 10.

As noted above, although the interface of the present invention has been shown and described as having two links, the interface 10 could be constructed with more than two links. For example, three connectors could be provided between the switch 14 and the interface 10, thus providing three links. In a three link interface, three device drivers and three protocol stacks would also be provided. The splitting task algorithm would receive data messages from three protocol stacks and would deliver these messages to the application task algorithm 48 for translation. When operating in the reverse direction, the combining task of a three link interface would deliver the message packets to three protocol stacks in an alternating fashion. In the event of a link failure in a three link interface, the remaining two links would continue to process the data messages. Additionally, if two of the three links failed, the remaining link would be available to process and translate the data messages.

While preferred embodiments of the present invention are shown and described, it is envisioned that those skilled

in the art may devise various modifications of the present invention without departing from the spirit and scope of the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2